



DENSETEC® LDPE



Low Density Polyethylene Sheet

APPLICATIONS

Trays

Orthotics

Chemical Industries

Environmental Barriers

Various Machined Parts

Rollers

Prosthetics


Cutting Surfaces

Stenciling Cut Outs

Shielding Applications



Smooth Finish



Planed Finish



DENSETEC®
LDPE



FEATURES

- Impact resistant
- Extremely flexible
- Chemical resistant
- Low tensile strength
- Can be certified to Mil-P-23536 A Type V
- Mil-P-23536 A Type V certified material is inspected per Mil-I-45208 A
- Very pliable
- Easily cleaned
- Soft to the touch
- Moisture resistant
- Corrosion resistant
- RoHS & REACH compliant

COLORS

- Natural* Black
- *FDA approved colors

SIZES

STANDARD:	<u>Extruded</u> <small>inch / mm</small>	<u>Compression Molded</u> <small>inch / mm</small>
Thickness	0.03 - 1 / 0.8 - 25	Not a Standard Product
Sheet Size	48 x 96 / 1220 x 2440 48 x 120 / 1220 x 3050	

CAPABILITIES:	<u>Extruded</u> <small>inch / mm</small>	<u>Compression Molded</u> <small>inch / mm</small>
Thickness	0.03 - 1.25 / 0.8 - 32	0.5 - 4 / 12.7 - 100
Width	45 - 144 / 1140 - 3655	48 - 96 / 1220 - 2440
Length	Up to 480 / 12200	Up to 240 / 6100

FINISH

- Smooth - standard extruded finish
- Planed - standard compression molded finish

Note: Other sizes, colors, formulations and forming grade available upon request

Distributed by:

P POLYMER INDUSTRIES

Headquarters:

PO Box 32; 10526 AL Hwy 40
Henagar, AL 35978 USA
Ph: (256) 657-5197
Fax: (256) 657-5189
Toll Free: 1-877-POLYMER (765-9637)

Mechanical Division: Pisgah, AL
Ultrapoly Division: Tacoma, WA
Midwest Distribution: Bolingbrook, IL
West Coast Distribution: Salt Lake City, UT
Avalanche Liner Division: Oxford, WI