



Homopolymer And Copolymer Polypropylene Sheet

APPLICATIONS

Tank Covers

Machine Parts

Fire Truck Tanks

Fume Hoods and Ducts

Acid Tanks and Liners

Pump Impellers and Casings

Structural Tanks for Chemicals Industry

Battery Cases

Cutting Boards

Plating Modules

Orthotics/Prosthetics

Laboratory Equipment

Filter Plate and Frames

Semiconductor Processing Equipment





Orange Peel Finish



Smooth Finish



Planed Finish



DENSETEC® POLYPROPYLENE







FEATURES

Acid resistant
Abrasion resistant
Chemical resistant
ROHS & REACH compliant
Alkalis and solvent resistant
Resistant to temps up to 180
degrees

Impact resistant
Moisture resistant
Stress crack resistant
Excellent dielectric properties
Able to retain stiffness and flexibility
Copolymer has higher impact strength
than homopolymer

COLORS

Natural* Blue/White**
White** Black
Euro Gray**

*FDA approved and NSF Standard 51 Certified
**FDA approved colors

SIZES

STANDARD: Extruded Compression Molded inch / mm

Thickness 0.03 - 1 / 0.8 - 25 Not a
Sheet Size 48 x 96 / 1220 x 2440 Standard

48 x 120 / 1220 x 3050 Product

Extruded inch / mm

Thickness 0.03 - 1.25 / 0.8 - 32 Width 45 - 144 / 1140 - 3655 Length Up to 480 / 12200

0.5 - 4 / 12.7 - 100 48 - 96 / 1220 - 2440 Up to 240 / 6100

Compression Molded

inch / mm

FINISH

CAPABILITIES:

Smooth - standard extruded finish
Orange peel - available extruded finish
Planed - standard compression molded finish

Note: Other sizes, colors, formulations, and forming grade available upon request. Homopolymer is the standard grade. Copolymer is available upon request.

Distributed by:



POLYMER INDUSTRIES

Headquarters:

PO Box 32; 10526 AL Hwy 40 Henagar, AL 35978 USA Ph: (256) 657-5197 Fax: (256) 657-5189

Toll Free: 1-877-POLYMER (765-9637)

Mechanical Division: Pisgah, AL
Ultrapoly Division: Tacoma, WA
Midwest Distribution: Bolingbrook, IL
West Coast Distribution: Salt Lake City, UT
Avalanche Liner Division: Oxford, WI