



POLYSLICK® MARINE



Ultra High Molecular Weight Polyethylene Fendering



Fender Pads



Flexi Fend®

U.S. Patent Nos. 6,832,570 /
6,948,440 / 7,624,694 / 8,029,209



Pileguard

APPLICATIONS

Dock Facings

Bridge Fenders

Boat Rails and Gunnels

Canal Lock Door Panels

Lock and Dam Guidewall

Dry Dock Walls and Side Rails

Pile Facings

Gate Fenders

Floating Docks

Pipeline Fenders

Wharf, Pier and Lock Fenders

Offshore Pump Station Fenders

Rub Rails

Sliding Pads

Pier Protection

Guide Rollers

Canal Lock Walls

Keel and Bilge Block Facings



POLYSLICK®
MARINE



UHMW-PE DOCK FENDERS AND FENDER PADS

FEATURES

Impact resistant
Abrasion resistant
UV protected
Will not corrode, rot or splinter

Resists marine borers and barnacle growth
Non-sparking
Can be drilled, chamfered and fabricated to meet customer specifications

COLORS

Black Yellow
Custom Colors

SIZES

Thickness inch / mm
0.125 to 10 / 3 to 250

UHMW-PE FLEXI FEND®

FEATURES

Non-marking
Non-grabbing
Absorbs energy
Impervious to salt water and oil
Leaf shape allows it to flex with impact and return to shape with no permanent damage

High visibility
Easy installation
Eliminates paint or tape
Will not corrode, rot or splinter
US patent nos. 6,832,570 / 6,948,440 / 7,624,694 / 8,029,209

COLORS

Black Gray
Custom Colors

SIZES

T x H x W	<u>inch / mm</u>	<u>inch / mm</u>
	0.25 x 4 x 2.13 / 6 x 100 x 53	0.5 x 10 x 4.2 / 12 x 250 x 105
	0.375 x 4 x 2.13 / 9.5 x 100 x 53	0.625 x 10 x 4.2 / 15 x 250 x 105
	0.375 x 10 x 4.2 / 9.5 x 250 x 105	1 x 10 x 4.2 / 25 x 250 x 105



UHMW-PE PILEGUARDS

FEATURES

Impact resistant
Abrasion resistant
UV protected
Will not corrode, rot or splinter

Resists marine borers and barnacle growth
Non-sparking
Can be drilled, chamfered and fabricated to meet customer specifications

COLORS

Black Yellow
Custom Colors

SIZES

Thickness inch / mm
1.25 / 32
Width x Length 12 x Up to 30 feet / 300 x Up to 9 meters

UHMW-PE CUSTOM FENDERS

Fenders can be fabricated, heat or cold formed to customer specifications.
Custom colors and formulations available.

Distributed by:

 **POLYMER INDUSTRIES**

Headquarters:

PO Box 32; 10526 AL Hwy 40
Henagar, AL 35978 USA
Ph: (256) 657-5197
Fax: (256) 657-5189
Toll Free: 1-877-POLYMER (765-9637)

Mechanical Division: Pisgah, AL
Ultrapoly Division: Tacoma, WA
Midwest Distribution: Bolingbrook, IL
West Coast Distribution: Salt Lake City, UT
Avalanche Liner Division: Oxford, WI